

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>Vehicle Configuration</b>		
CASCADIA 125" SLEEPER CAB 2011 MODEL YEAR SPECIFIED SET BACK AXLE - TRACTOR LH PRIMARY STEERING LOCATION	9,550	7,560
<b>Engine</b>		
CUM ISX 500 @ 2000 RPM, 1850 LB/FT @ 1200 RPM	200	30
<b>Engine Equipment</b>		
<b>2007 EPA/CARB EMISSION CERTIFICATION</b>		
ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER LOWER WINDSHIELD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (4) ALLIANCE ABSORBED GLASS MAT MODEL 9A31, GROUP 31, 12 VOLT MAINTENANCE FREE 3700 CCA THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED LONG SIDE TO RAIL, CAB WIDTH SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB WIRE GROUND RETURN FOR BATTERY CABLES NON-POLISHED DIAMOND PLATE BATTERY BOX COVER POSITIVE POWER CIRCUIT SHUTOFF SWITCH IN CAB MOUNTED OUTBOARD OF DRIVER SEAT PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS	8	



Description	Weight Front	Weight Rear
EATON FULLER 15-1/2 INCH CERAMIC SOLO VCTPLUS ADJUSTMENT FREE CLUTCH		
TORQUE LIMITING CLUTCH BRAKE		
ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING		
CUMMINS 18.7 CFM COMPRESSOR WITH INTERNAL SAFETY VALVE		
TEFLON COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
CUMMINS INTEBRAKE COMPRESSION BRAKE WITH DASH SWITCH		
RH INBOARD FRAME MOUNTED HORIZONTAL AFTERTREATMENT DEVICE WITH RH BACK OF CAB FRAME MOUNTED VERTICAL TAILPIPE ROUTED OVER FRAME		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
13 FOOT 06 INCH (162 INCH+0/-5 INCH) EXHAUST SYSTEM HEIGHT		
BRIGHT UPPER STACK(S)		
RH CURVED VERTICAL TAILPIPE BACK OF CAB FRAME MOUNTED ROUTED BETWEEN RAILS OVER FRAME		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD		
HORTON DRIVEMASTER ON/OFF FAN DRIVE AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
FULL FLOW OIL FILTER		
FLEETGUARD PLAIN COOLANT FILTER	10	
1625 SQUARE INCH ALUMINUM RADIATOR		
ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PREHEATER	4	



Description	Weight Front	Weight Rear
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>		
EATON FULLER RTLO-18918B TRANSMISSION	90	30
<b>Transmission Equipment</b>		
ALUMINUM CLUTCH HOUSING		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN		
PAINTED SHIFT LEVER, SOLID LINKAGE		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
SYNTHETIC SAE 50W TRANSMISSION LUBE		
<b>Front Axle and Equipment</b>		
MFS-14-143A 14,700# FF1 SINGLE FRONT AXLE	60	
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	60	
NON-ASBESTOS FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		
VENTED FRONT HUB CAPS - OIL		
PRO-TORQ SPINDLE NUTS - ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
14,000# TAPERLEAF FRONT SUSPENSION	60	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		



Description	Weight Front	Weight Rear
RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE		450
4.10 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
18N MERITOR MAIN DRIVELINE WITH FULL ROUND YOKES	20	20
17N MERITOR INTERAXLE DRIVELINE WITH FULL ROUND YOKES		
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		40
(1) DCDL FORWARD-REAR AXLE VALVE, (1) REAR-REAR AXLE VALVE AND (1) INTERAXLE LOCK CONTROL VALVE		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		20
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
CHICAGO RAWHIDE SCOTSEAL PLUS XL REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		20
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
SYNTHETIC 75W-90 REAR AXLE LUBE		

### Rear Suspension

AIRLINER 46,000# REAR SUSPENSION WITH CHAIN CLEARANCE		420
AIRLINER HIGH POSITION RIDE HEIGHT		
AXLE SEATS WITH RETAINERS		
55 INCH AXLE SPACING		
MANUAL DUMP VALVE FOR AIR SUSPENSION WITH INDICATOR LIGHT AND GAUGE		
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		

### Brake System



Description	Weight Front	Weight Rear
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER		
STEEL AIR BRAKE RESERVOIRS		
PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		

### Trailer Connections

15 FOOT COILED TRAILER AIR HOSE WITH 12 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
36 INCH STAINLESS STEEL SLIDE BAR WITH SPRING TYPE AIR HOSE HANGER		
COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER MOUNTED LH BACK OF CAB WITH GROUND ACCESS		
PRIMARY CONNECTOR/RECEPTACLE CENTER PIN POWERED THROUGH IGNITION		
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED LOWER LH BACK OF CAB		
SUPPLEMENTAL ISO 3731 7-WAY RECEPTACLE LOCATED WITH PRIMARY RECEPTACLE		
15 FOOT DETACHABLE COILED PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR WITH 12 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
15 FOOT DETACHABLE COILED SUPPLEMENTAL TRAILER ELECTRICAL CABLE; ISO 3731 7-WAY WITH 12 INCH TRACTOR, 12 INCH TRAILER LEADS	12	

### Wheelbase & Frame

6200MM (244 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	90	40
1450MM (57 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH		
UNDERSLUNG CROSSMEMBER		
FLANGED TAPERED END OF FRAME		
STANDARD WEIGHT ENGINE CROSSMEMBER		



Description	Weight Front	Weight Rear
STANDARD REAR MOST CROSSMEMBER		
HEAVY DUTY SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
LH AND RH BACK OF CAB ACCESS	5	5
28 INCH (700MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS	2	2
PAINTED AERODYNAMIC BUMPER		
CENTER STEP RECESSED IN BUMPER		
REMOVABLE FRONT TOW HOOKS STORED ON CHASSIS FRAME		
BUMPER MOUNTING FOR (3) LICENSE PLATES		
BETTS B-7 STAINLESS STEEL MUDFLAP BRACKETS		10
BLACK MUDFLAPS		
FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS		
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS		
PLAIN RH 33X25X13 INCH CAB ENTRY TOOL BOX WITH DIAMOND PLATE COVER	50	50
<b>Fifth Wheel</b>		
HOLLAND FW35 ILS 24.0 INCH AIR SLIDE FIFTH WHEEL - 2 INCH SLIDE INCREMENTS		20
FIFTH WHEEL 457MM (18.0 INCHES) AHEAD OF SUSPENSION CENTERLINE		
194MM (7.62 INCH) FIFTH WHEEL HEIGHT		
OUTBOARD ANGLE - FIFTH WHEEL MOUNTING		
DASH MOUNTED CONTROL VALVE AND PLUMBING FOR FIFTH WHEEL		
LH FIFTH WHEEL RELEASE		
FIFTH WHEEL RAMPS (BOX CONSTRUCTION)		50
<b>Fuel Tanks</b>		
150 GALLON/567 LITER ALUMINUM FUEL TANK - RH	35	35
150 GALLON/567 LITER ALUMINUM FUEL TANK - LH	20	20
23 INCH DIAMETER FUEL TANK(S)		
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS		
FUEL TANK(S) AFT	-30	30
PLAIN STEP FINISH		
CHROME FUEL TANK CAP(S)		



Description	Weight Front	Weight Rear
ALLIANCE FUEL FILTER/WATER SEPARATOR EQUIFLO INBOARD FUEL SYSTEM REINFORCED NYLON FUEL HOSE	15	
<b>Tires</b>		
MICHELIN XZA3 11R24.5 14 PLY RADIAL FRONT TIRES	30	
MICHELIN XDN2 11R24.5 14 PLY RADIAL REAR TIRES		216
<b>Hubs</b>		
CONMET PRE-SET BEARING ALUMINUM FRONT HUBS CONMET PRE-SET BEARING ALUMINUM REAR HUBS		
<b>Wheels</b>		
ALCOA 98364XDF 24.5X8.25 10-HUB PILOT DURAFLLANGE ALUMINUM DISC FRONT WHEELS	-46	
ALCOA 98364XDF 24.5X8.25 10-HUB PILOT DURAFLLANGE ALUMINUM DISC REAR WHEELS POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY NO POLISHED PUSHER/TAG WHEELS		-184
<b>Cab Exterior</b>		
125 INCH BBC ALUMINUM CONVENTIONAL CAB RH CAB DOOR(S) WITH 70 DEGREE DOOR STOP LH CAB DOOR(S) WITH 70 DEGREE DOOR STOP 72 INCH XT SLEEPERCAB	-100	-100
12 INCH CAB/SLEEPERCAB SIDE EXTENDERS WITH BLACK FLEXIBLE ENDS UNDER CAB VANITY PANELS LH AND RH BAGGAGE DOORS AIR CAB MOUNTS NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE LH AND RH INTERIOR GRAB HANDLES CHROME GRILLE WITH INTEGRAL SURROUND AERODYNAMIC HOOD HOOD AND TUNNEL/FIREWALL PREMIUM NOISE ABATEMENT AND INSULATION	5	
DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	4	



Description	Weight Front	Weight Rear
SINGLE ELECTRIC HORN		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY		
VISOR MOUNTED LED MARKER LIGHTS		
AUXILIARY HIGH BEAM LIGHTS RECESSED IN BUMPER	6	
DAYTIME RUNNING LIGHTS		
FREIGHTLINER LED FLANGE MOUNTED STOP/TAIL/TURN LIGHTS WITH SEPARATE INCANDESCENT BACKUP LIGHTS		5
STANDARD SIDE TURN SIGNAL		
(2) SWIVEL UTILITY LIGHTS HIGH INBOARD ON SIDE EXTENDERS AND (2) FLUSH MOUNTED BACK OF CAB/SLEEPER	6	
DUAL BRIGHT FINISH HEATED MIRRORS WITH INTEGRAL CONVEX AND LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
RH DOWN VIEW MIRROR		
NO AUXILIARY MIRROR	-8	
STANDARD SIDE/REAR REFLECTORS		
REAR REFLECTIVE DEVICE		
NO SLEEPER VENT		
EXTERIOR SUN VISOR	20	
SOLAR TINTED DOOR GLASS LH AND RH WITH TINTED FORWARD SIDE GLASS		
RH AND LH ELECTRIC POWERED WINDOWS		
LH AND RH TINTED AND SCREENED SLIDING WINDOWS	20	
2-PIECE SOLAR TINTED CURVED ROPED-IN WINDSHIELD		
8 LITER WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR		
WHITE WINTERFRONT	2	
<b>Cab Interior</b>		
PREMIUM TAN VINYL INTERIOR		
UPGRADE LH DOOR TRIM		
UPGRADE RH DOOR TRIM		
BLACK MATS		
CARPET IN SLEEPER AREA	-10	
BLACK MATS IN BAGGAGE COMPARTMENT		



Description	Weight Front	Weight Rear
(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY		
TALL CLOSET WITH STORAGE CABINET		
MID-LEVEL REFRIGERATOR CABINET WITH TV SHELF AND STORAGE CABINET		
FORWARD ROOF MOUNTED CONSOLE WITH CENTER LOCKING DOOR		
STORAGE CABINET WITH DOORS, BACK OF SLEEPER	20	15
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
STORAGE POCKET(S) MOUNTED INSIDE CABINET DOOR(S) WITH ONE MIRROR		
40 INCH WIDE LIFTABLE LOWER BUNK		
NO UPPER BUNK	-50	-50
TENT STYLE BUNK RESTRAINT FOR LOWER BUNK		
DIGITAL FLUSH MOUNTED ALARM CLOCKS IN DASH AND SLEEPER		
NO CUP/THERMOS HOLDER		
PARCHMENT/SHALE WING DASH		
2-1/2 LB. FIRE EXTINGUISHER	5	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
AUXILIARY HEATER/AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
STANDARD HEATER PLUMBING		
SANDEN HEAVY DUTY AIR CONDITIONER COMPRESSOR		
RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOOR AND BUNK ACTIVATED BAGGAGE COMPARTMENT LIGHTING SYSTEM		
PREMIUM CAB LIGHTING		
PREMIUM SLEEPER LIGHTING		
LH AND RH ELECTRIC DOOR LOCKS		
SPRING MATTRESS IN SLEEPER		



Description	Weight Front	Weight Rear
CAB PRIVACY CURTAIN	5	
BUILT-IN REFRIGERATOR	20	20
TRIANGULAR REFLECTORS WITHOUT FLARES MOUNTED IN LH BAGGAGE COMPARTMENT	10	
ELITE HIGH BACK AIR SUSP DRIVER SEAT WITH HEAT, 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FWD AND REAR CUSHION TILT, ADJUSTABLE SHOCK AND SWIVEL BASE		
ELITE HIGH BACK AIR SUSP PASS SEAT WITH HEAT, 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FWD AND REAR CUSHION TILT, ADJUSTABLE SHOCK AND SWIVEL BASE		
BLACK SUSPENSION COVER FOR DRIVER AND PASSENGER SEATS	4	
DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
MORDURA CLOTH DRIVER SEAT		
MORDURA CLOTH PASSENGER SEAT		
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
SLEEPER CURTAIN		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH SWITCHES		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

### Instruments & Controls

BRIGHT ARGENT FINISH GAUGE BEZELS  
PREMIUM WOODGRAIN DRIVER INSTRUMENT  
PANEL  
LOW AIR PRESSURE LIGHT AND BUZZER  
(1) TRACTOR AND (1) TRAILER BRAKE  
APPLICATION AIR GAUGE  
2 INCH PRIMARY AND SECONDARY AIR  
PRESSURE GAUGES  
DASH MOUNTED AIR RESTRICTION INDICATOR  
WITH GRADUATIONS  
ELECTRONIC CRUISE CONTROL WITH  
CONTROLS ON STEERING WHEEL SPOKES  
KEY OPERATED IGNITION SWITCH AND  
INTEGRAL START POSITION; 4 POSITION  
OFF/RUN/START/ACCESSORY



Description	Weight Front	Weight Rear
ICU4 1X7 ODOMETER DISPLAY WITH DIAGNOSTICS, 16 WARNING LAMPS AND DATA LINKED		
DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1587/1708/1939, LOCATED BELOW DASH		
2 INCH ELECTRIC FUEL GAUGE		
DUAL REAR AXLE TEMPERATURE GAUGES WITH SENSOR SHIELD		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
ENGINE OIL TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
DELPHI AM/FM/WB/SIRIUS PREMIUM RADIO WITH CD	10	
DASH MOUNTED RADIO		
STANDARD SPEAKER SYSTEM		
COBRA 29LTDST FACTORY INSTALLED CB RADIO	5	
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION WITH FACE PLATE		
DUAL SIDE MOUNT MULTI-BAND AM/FM/CB ANTENNA SYSTEM		
INTEROPERABLE SDAR ANTENNA		
TELEVISION ANTENNA		
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
IGNITION SWITCH CONTROLLED ENGINE STOP		
TWO EXTRA SWITCHES IN DASH WITH INDICATOR LAMP AND WIRE TO CHASSIS AT BACK OF CAB/SLEEPER		
STEERING WHEEL MOUNTED ELECTRIC HORN CONTROL		
BW TRACTOR PROTECTION VALVE		
TRAILER HAND CONTROL BRAKE VALVE		
2 INCH TURBO AIR PRESSURE GAUGE		



Description	Weight Front	Weight Rear
2 INCH VOLTMETER		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: L3761EB FLAME RED ELITE BC  
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT  
 BUMPER PAINTED SAME AS FENDERS/LOWER SECTION OF CAB  
 SUNVISOR PAINTED SAME AS CAB COLOR A

**Certification / Compliance**

CANADA CMVSS CERTIFICATION

**TOTAL VEHICLE SUMMARY**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	10282 LBS	8784 LBS	19066 LBS
Total Weight <sup>+</sup>	10282 LBS	8784 LBS	19066 LBS

**ITEMS NOT INCLUDED IN ADJUSTED LIST PRICE**



## Other Factory Charges

DELIVERY & ORDER PROCESSING CHARGE

## Extended Warranty

EXTENDED TRANSMISSION COVERAGE UPGRADE 3 YEARS OR  
300,000 MILES/480 000 KM

EXTENDED FRONT/REAR AXLES COVERAGE UPGRADE 3  
YEARS/300,000 MILES/480 000 KM

FRAME RAIL/CROSSMEMBER EXTENDED WARRANTY, 6  
YEAR/750,000 MILE/1 200 000 KM

CAB AND HOOD EXTENDED WARRANTY 3 YEARS/200,000  
MILES/320 000 KM

TOWING EXTENDED/ROADSIDE SERVICE WARRANTY, 1  
YEAR/UNLIMITED MILEAGE

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

