

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Vehicle Configuration		
CORONADO SD CONVENTIONAL CHASSIS 2011 MODEL YEAR SPECIFIED	8,760	6,930
SET FORWARD AXLE - TRACTOR LH PRIMARY STEERING LOCATION	-435	480
Engine		
DD15 14.8L 560 HP @ 1800 RPM, 2000 GOV RPM, 1850 LB/FT @ 1100 RPM		
Engine Equipment		
2010 EPA/CARB EMISSION CERTIFICATION NO 2008 CARB EMISSION CERTIFICATION ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER		
DUAL SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED HIGH CAPACITY AIR CLEANER AND DUAL PASSIVE PRECLEANERS	10	
DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE		
(4) ALLIANCE ABSORBED GLASS MAT MODEL 8A31, GROUP 31, 12 VOLT MAINTENANCE FREE 3200 CCA THREADED STUD BATTERIES STEEL BATTERY BOX WITH ENCLOSED TRAY SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB	50	20
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN POLISHED DIAMOND PLATE BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	



Description	Weight Front	Weight Rear
DELCO REMY/SURE POWER LOW VOLTAGE BATTERY DISCONNECT AT 12.3 VOLTS FOR ISOLATED CIRCUITS WITH ONE MINUTE ALARM	2	
EATON FULLER 15-1/2 INCH CERAMIC EASY PEDAL XL VCTPLUS MANUALLY ADJUSTED CLUTCH		
TORQUE LIMITING CLUTCH BRAKE		
ZERK FITTINGS WITH EXTENSION HOSES AT CLUTCH RELEASE BEARING AND X-SHAFT		
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL WARNING AND DERATE PROTECTION SYSTEM		
JACOBS COMPRESSION BRAKE		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH DUAL CAB MOUNTED VERTICAL TAILPIPES		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
13 FOOT 06 INCH (162 INCH+0/-5 INCH) EXHAUST SYSTEM HEIGHT		
BRIGHT UPPER STACK(S)		
DUAL CURVED VERTICAL TAILPIPES B-PILLAR MOUNTED		
23 GALLON DIESEL EXHAUST FLUID TANK POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER	25	
DUAL STAINLESS STEEL MUFFLER/TAILPIPE SHIELDS		
HORTON DRIVEMASTER ON/OFF FAN DRIVE AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
FULL FLOW OIL FILTER		
DDC SUPPLIED COOLANT FILTER, ENGINE MOUNTED		
1700 SQUARE INCH ALUMINUM RADIATOR ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE-CHARGED SCA HEAVY DUTY COOLANT	-20	



Description	Weight Front	Weight Rear
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
GATES POWERGRIP SHRINK BAND HOSE CLAMPS WHERE POSSIBLE		
RADIATOR DRAIN VALVE		
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PREHEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
DELCO 12V 39MT+ HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		

Transmission

EATON FULLER RTLO-18918B TRANSMISSION	90	30
---------------------------------------	----	----

Transmission Equipment

CAST IRON CLUTCH HOUSING		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN		
PAINTED SHIFT LEVER, SOLID LINKAGE		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK	15	
SYNTHETIC SAE 50W TRANSMISSION LUBE		

Front Axle and Equipment

MFS-14-143A 14,700# FF1 SINGLE FRONT AXLE	60	
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
CHICAGO RAWHIDE SCOTSEAL PLUS XL FRONT OIL SEALS		
VENTED FRONT HUB CAPS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
STANDARD KING PIN BUSHINGS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		



Description	Weight Front	Weight Rear
2 QUART SEE THROUGH POWER STEERING RESERVOIR ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE		
Front Suspension		
14,600# TAPERLEAF FRONT SUSPENSION	120	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
RT-46-164P 46,000# R-SERIES TANDEM REAR AXLE		500
4.10 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
18N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES	50	50
17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES		
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		40
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AXLE VALVE AND (1) REAR-REAR AXLE VALVE		
INDICATOR LIGHT AND BUZZER FOR EACH MODE SWITCH		
INDICATOR LIGHT AND BUZZER FOR EACH MODE SWITCH		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		20
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
CHICAGO RAWHIDE SCOTSEAL PLUS XL REAR OIL SEALS		
NO DRIVELINE PARKING BRAKE		
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		



Description	Weight Front	Weight Rear
SYNTHETIC 75W-90 REAR AXLE LUBE		
Rear Suspension		
AIRLINER 46,000# REAR SUSPENSION WITH CHAIN CLEARANCE		420
AIRLINER HIGH POSITION RIDE HEIGHT		
AXLE SEATS WITH RETAINERS		
59.06 INCH (1500MM) AXLE SPACING		
MANUAL DUMP VALVE FOR AIR SUSPENSION WITH INDICATOR LIGHT AND GAUGE		
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		
Brake System		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
BENDIX OIL COALESCING FILTER FOR AIR DRYER		
STEEL AIR BRAKE RESERVOIRS		
PULL CABLES ON ALL AIR RESERVOIR(S)		
Trailer Connections		
15 FOOT COILED TRAILER AIR HOSE WITH 12 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
36 INCH STAINLESS STEEL SLIDE BAR WITH SPRING TYPE AIR HOSE HANGER	2	
COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER		
PRIMARY CONNECTOR/RECEPTACLE CENTER PIN POWERED THROUGH IGNITION		
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED ON CHASSIS BACK OF CAB/SLEEPER		
SUPPLEMENTAL ISO 3731 7-WAY RECEPTACLE LOCATED WITH PRIMARY RECEPTACLE		



Description	Weight Front	Weight Rear
20 FOOT DETACHABLE COILED PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR WITH 48 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
12 FOOT DETACHABLE STRAIGHT SUPPLEMENTAL TRAILER ELECTRICAL CABLE; ISO 3731 7-WAY	10	
Wheelbase & Frame		
6200MM (244 INCH) WHEELBASE		
7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	850	-70
1525MM (60 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH		
FLANGED TAPERED END OF FRAME		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
HEAVY DUTY SUSPENSION CROSSMEMBER		
Chassis Equipment		
LH AND RH BACK OF CAB ACCESS	5	5
28 INCH (700MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS	2	2
12 INCH CHROMED STEEL 3/8 INCH LOGGER BUMPER WITH CENTER TOW DEVICE	110	-25
HEAVY DUTY CENTER MOUNTED TOW PIN		
SINGLE LICENSE PLATE BRACKET BELOW BUMPER		
FLEETLINE SF3045PCX MITERED MUDFLAP BRACKETS		20
BLACK MUDFLAPS		
FRONT CAB MOUNTED MUDFLAPS AND HOOD MOUNTED SPLASH SHIELDS		
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS		
Fifth Wheel		
HOLLAND FW0070 EXTRA CAPACITY CORRUGATED PLATE MOUNTED STATIONARY FIFTH WHEEL		70
FIFTH WHEEL 102MM (04.0 INCHES) AHEAD OF SUSPENSION CENTERLINE		
227MM (8.94 INCH) FIFTH WHEEL HEIGHT		5
PLATE MOUNT - FIFTH WHEEL MOUNTING		



Description	Weight Front	Weight Rear
LH FIFTH WHEEL RELEASE MANUAL SECOND LOCK		
Fuel Tanks		
150 GALLON/567 LITER ALUMINUM FUEL TANK - RH	130	20
150 GALLON/567 LITER ALUMINUM FUEL TANK - LH	20	20
25 INCH DIAMETER FUEL TANK(S) POLISHING OF FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS FUEL TANK(S) AFT POLISHED STEP FINISH CHROME FUEL TANK CAP(S) EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires		
CUSTOMICHELIN XZE2 11R24.5 16 PLY RADIAL FRONT		
MICHELIN XDY-EX 11R24.5 16 PLY RADIAL REAR TIRES		280
Hubs		
CONMET PRE-SET BEARING ALUMINUM FRONT HUBS CONMET PRE-SET BEARING ALUMINUM REAR HUBS		
Wheels		
ALCOA 98560XDF 24.5X8.25 10-HUB PILOT HD DURAFLANGE ALUMINUM DISC FRONT WHEELS	-26	
ALCOA LVL ONE 98367XDF 24.5X8.25 10-HUB PILOT DURAFLANGE ALUMINUM DISC REAR WHEELS POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		-184
Cab Exterior		
122 INCH BBC CONVENTIONAL ALUMINUM CAB RH CAB DOOR(S) WITH 70 DEGREE DOOR STOP LH CAB DOOR(S) WITH 70 DEGREE DOOR STOP 58 INCH MID-ROOF SLEEPER CAB 22 INCH LH AND RH BAGGAGE DOORS WITH INTERIOR PULL CABLE	260	310



Description	Weight Front	Weight Rear
AIR CAB MOUNTS NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE AND FRONT REMOVABLE GRILLE MOUNTED BUGSCREEN LH AND RH EXTERIOR GRAB HANDLES EXHAUST MOUNTED WITH INTERIOR GRAB HANDLES BRIGHT FINISH BEZEL WITH STYLIZED TILT HANDLE		
STAINLESS STEEL GRILLE CHROMED HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS FULL FENDER HOOD WITH BRIGHT LOWER COWLSIDES AND REINFORCED FENDERS	2	
ENGINE COMPARTMENT PREMIUM NOISE ABATEMENT AND INSULATION		
FOUR 29 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS SINGLE ELECTRIC HORN	12	
FOUR HORN SHIELDS DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
REAR LICENSE PLATE MOUNT END OF FRAME HALOGEN COMPOSITE HEADLAMPS		
FREIGHTLINER LED MARKER LIGHTS INTEGRAL WITH EXTERIOR SUN VISOR		
LED ACCENT LIGHTS ON HOOD AIR INTAKES AND LOWER EDGE OF CAB AND SLEEPER CUSTOMER FURNISHED ROADLAMPS - WIRING, SWITCH AND BRACKETS ONLY AND OMIT BUMPER CUTOUTS	15	
DAYTIME RUNNING LIGHTS TRUCK-LITE 40 STOP/TAIL WITH SEPARATE BACKUP LIGHTS GROMMET MOUNTED		5
STANDARD FRONT TURN SIGNAL LAMPS SWITCH, INDICATOR LIGHT AND APPROXIMATELY 10 FEET OF WIRE ON CHASSIS LH AT BACK OF CAB FOR CUSTOMER FURNISHED UTILITY LIGHT(S)		
DUAL BRIGHT FINISH HEATED AERODYNAMIC MIRRORS WITH INTEGRAL CONVEX, LIGHTS AND DUAL AXIS LH AND RH REMOTE		
DOOR MOUNTED MIRRORS 102 INCH EQUIPMENT WIDTH		



Description	Weight Front	Weight Rear
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
REAR REFLECTIVE DEVICE		
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER		
(2) CHROME SLEEPER VENTS, LH AND RH		
STAINLESS STEEL EXTERIOR SUN VISOR WITH INTEGRAL MARKER LIGHTS	15	
NO REAR WINDOW		
TINTED DOOR GLASS		
RH AND LH ELECTRIC POWERED WINDOWS		
2-PIECE TINTED CURVED BONDED WINDSHIELD		
8 LITER WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR		
WHITE WINTERFRONT	2	

Cab Interior

OPAL GRAY CHAPARRAL VINYL INTERIOR		
SIGNATURE TUMBLEWEED TAN HARD TRIM		
LH DOOR TRIM WITH ADDITIONAL ARCTIC SEAL PACKAGE		
RH DOOR TRIM WITH ADDITIONAL ARCTIC SEAL PACKAGE		
CAB BLACK FLOOR MATS WITH PREMIUM NOISE ABATEMENT AND INSULATION		
COLOR COORDINATED CARPET WITH PREMIUM NOISE ABATEMENT AND INSULATION IN SLEEPER		
FULL UNDER BUNK/BAGGAGE COMPARTMENT LINER WITH BLACK MATS, PREMIUM NOISE ABATEMENT/INSULATION AND REMOVABLE PARTITIONS		
DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE		
LH LOWER TALL STORAGE CABINET WITH ATTACHED MID CABINET DRAWER AND DOORS	30	
RH LOWER SHORT CABINET WITH 1 REMOVABLE SHELF AND DOORS	5	5
RH UPPER SHORT TELEVISION CABINET MOUNTED TO ROOF		
FORWARD ROOF MOUNTED CONSOLE WITH LOCKING DOORS RH AND LH		



Description	Weight Front	Weight Rear
WRAPAROUND STORAGE SHELF WITH DOORS BACK AND SIDES OF SLEEPER	20	15
LH AND RH DOOR MAP POCKETS		
CLOTHES ROD IN SLEEPER		
35 INCH WIDE LIFTABLE LOWER BUNK		
LOWER BUNK RESTRAINT		
DIGITAL FLUSH MOUNTED ALARM CLOCK IN SLEEPER WITH ANALOG CLOCK IN OVERHEAD CONSOLE		
(3) CUP HOLDERS, LH, CENTER AND RH DASH		
AGATE/TUMBLEWEED TAN WING DASH		
2-1/2 LB. FIRE EXTINGUISHER	5	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
HVAC DUCTING WITH MAIN FRESH AIR FILTER		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
AUXILIARY HEATER/AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
STANDARD PLUMBING WITH INSULATED AUXILIARY HEATER PLUMBING UNDER CAB DECK ONLY		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
BINARY CONTROL, R-134A		
EXTREME CLIMATE THERMAL CAB AND SLEEPER INSULATION	30	30
CIRCUIT FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOOR AND BUNK ACTIVATED LH AND RH BUNK MOUNTED BAGGAGE COMPARTMENT LIGHTS		
DOOR ACTIVATED DOME/RED MAP LIGHTS LH AND RH OVERHEAD, COURTESY LIGHTS IN EACH DOOR AND FOOT WELL LIGHTS LH AND RH WITH DASH SWITCH		
(1) DOME LIGHT AND (1) READING LIGHT WITH DASH AND BUNK SWITCHES		
LH AND RH ELECTRIC DOOR LOCKS		
80X34X8 INCH QUILTED SPRING MATTRESS IN SLEEPER	15	15



Description	Weight Front	Weight Rear
(2) 12 VOLT POWER OUTLETS IN SLEEPER PANEL AND TV SHELF		
CAB PRIVACY CURTAIN	5	
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
NATIONAL 2000 SERIES HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 6 WAY FRONT AND REAR CUSHION ADJUSTMENT, 3 CHAMBER AIR LUMBAR, ACTIVE CUSHION AND BOLSTER	10	
NATIONAL 2000 SERIES HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH 6 WAY FRONT AND REAR CUSHION ADJUSTMENT, 3 CHAMBER AIR LUMBAR, ACTIVE CUSHION AND BOLSTER	35	10
BLACK VINYL SUSPENSION COVER FOR AIR DRIVER AND PASSENGER SEATS	4	
DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
MORDURA CLOTH DRIVER SEAT		
MORDURA CLOTH PASSENGER SEAT		
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
SLEEPER CURTAIN		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
4-SPOKE 18 INCH (450MM) LEATHER AND WOOD RIM STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS WITH VANITY MIRRORS		

Instruments & Controls

BRIGHT ARGENT FINISH GAUGE BEZELS
 OREGON BURL DRIVER INSTRUMENT PANEL
 OREGON BURL CENTER INSTRUMENT PANEL
 LOW AIR PRESSURE LIGHT AND BUZZER
 (1) TRACTOR AND (1) TRAILER BRAKE
 APPLICATION AIR GAUGE
 2 INCH PRIMARY AND SECONDARY AIR
 PRESSURE GAUGES
 INTAKE MOUNTED AIR RESTRICTION
 INDICATOR WITH GRADUATIONS
 ELECTRONIC CRUISE CONTROL WITH
 SWITCHES ON AUXILIARY GAUGE PANEL (B
 DASH PANEL)
 KEY OPERATED IGNITION SWITCH AND
 INTEGRAL START POSITION; 4 POSITION
 OFF/RUN/START/ACCESSORY



Description	Weight Front	Weight Rear
ICU4M DRIVER MESSAGE CENTER WITH 2X20 DISPLAY, WHITE FACE GAUGES, KEYPAD, DIAGNOSTICS AND DATA LINKED		
DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH		
2 INCH ELECTRIC FUEL GAUGE		
PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
ENGINE OIL TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
OVERHEAD INSTRUMENT PANEL		
STANDARD SMALL FACE PYROMETER	2	
AM/FM/WB RADIO WITH CD PLAYER AND FRONT AUXILIARY INPUT	10	
DASH MOUNTED RADIO		
(4) RADIO SPEAKERS: (1) COAXIAL IN EACH DOOR AND (2) COAXIALS IN SLEEPER		
COBRA 29LTDST FACTORY INSTALLED CB RADIO	5	
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION WITH FACE PLATE		
MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNTED ANTENNA SYSTEM		
TELEVISION ANTENNA	2	
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
IGNITION SWITCH CONTROLLED ENGINE STOP		
TWO EXTRA SWITCHES IN DASH WITH INDICATOR LAMP AND WIRE TO CHASSIS AT BACK OF CAB/SLEEPER		
BW TRACTOR PROTECTION VALVE		
TRAILER HAND CONTROL BRAKE VALVE		
2 INCH TURBO AIR PRESSURE GAUGE		



Description	Weight Front	Weight Rear
2 INCH VOLTMETER		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
MARKER LIGHT/HEADLIGHT SWITCH WITH SEPARATE INTERRUPTER FOR CLEARANCE LIGHTS		
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
GROTE TURN SIGNAL SWITCH WITH DIMMER		
12 BULB 25 AMP HEAVY DUTY ELECTRONIC FLASHER		

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0328EB DK CONCORD BLUE MET ELITE BC
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

Certification / Compliance

CANADA CMVSS CERTIFICATION

Secondary Factory Options

CORPORATE PDI CENTER OPTION
 INSTALLATION/MODIFICATION ONLY

TOTAL VEHICLE SUMMARY

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	10419 LBS	9033 LBS	19452 LBS
Total Weight ⁺	10419 LBS	9033 LBS	19452 LBS

ITEMS NOT INCLUDED IN ADJUSTED LIST PRICE



Other Factory Charges

2010 ENGINE EMISSIONS ESCALATOR
DELIVERY & ORDER PROCESSING CHARGE

Extended Warranty

EXTENDED TRANSMISSION COVERAGE UPGRADE 3 YEARS OR
300,000 MILES/480 000 KM

EXTENDED FRONT/REAR AXLES COVERAGE UPGRADE 3
YEARS/300,000 MILES/480 000 KM

FRAME RAIL/CROSSMEMBER EXTENDED WARRANTY, 6
YEAR/750,000 MILE/1 200 000 KM

CAB AND HOOD EXTENDED WARRANTY 3 YEARS/375,000
MILES/600 000 KM

TOWING EXTENDED/ROADSIDE SERVICE WARRANTY, 1
YEAR/UNLIMITED MILEAGE

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

